

# Super MP2 Graphite Grease

## TECHNICAL PRODUCT INFORMATION



### **Multipurpose NLGI 2 Graphite Fortified Grease**

**Super S Super MP2 Graphite Grease** is a multipurpose NLGI #2 lithium-based grease fortified with graphite. It exhibits good mechanical stability, rust inhibition and water resistance. It is an excellent general purpose lubricant for household, workshop and everyday applications, and may be more suitable for use in many cases than dry powdered graphite or basic household oils. It has a broad range of applications in automotive chassis and off-highway, over-the-road and industrial vehicles and equipment, as well as other general lubrication where a heavy grease with solid lubricants is required.

#### **FEATURES/ BENEFITS**

- **Good resistance to water washout** - Super MP2 Graphite Grease holds lubrication in place and keeps it from being washed away from lubricated surfaces.
- **Long service life** - Super MP2 Graphite Grease keeps lubrication on surfaces longer than oils or dry powders.
- **Protects against wear, oxidation/rust and corrosion** - Super MP2 Graphite Grease protects surfaces from the damaging effects of exposure to water, air and many cleaners and chemicals.

#### **APPLICATIONS**

**Super S Super MP2 Graphite Grease** is designed for lubrication of spring leaves, handbrake cables, flexible drives, exposed chains, universal joints, chassis and ball & roller bearings.

It is recommended for:

- slow speed plain bearings and slides where heavy grease with solid lubricants is required
- construction equipment including bulldozers, scrapers, loading shovels, and dump trucks where graphite grease is recommended and high temperature capability is not required
- plain bearing locks, latches and fasteners, cables and springs, plain bearing locks, latches and fasteners
- bicycle chains, bolt threads, swings and recreational equipment, garage doors, lawn mowers and other home and workshop needs
- fifth wheel lubricant

#### **SPECIAL HANDLING, NOTICES OR WARNINGS**

None required

#### **TYPICAL CHARACTERISTICS**

<b>Super S Super MP2 Graphite Grease</b>	
<i>Properties</i>	<i>Data</i>
Appearance	grey/black
Soap Type	Lithium
NLGI Grade	#2
Drop Point (°C)	>171°C
Graphite Content %	>15

#### **PRODUCT NUMBERS**

SUS 204      50/ 14oz tubes