

Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR

---

**1. MATERIAL AND COMPANY IDENTIFICATION**

**Material Name** : Super S Air Tool Oil  
**Uses** : Air Tool Oil

**Manufacturer/Supplier** : Smitty's Supply, Inc.  
PO Box 530  
Roseland, LA 70456  
USA

**MSDS Request** : 985-748-9687

**Emergency Telephone Number** : 800-424-9300 – toll free in the U.S., Canada, and  
**CHEMTREC** U.S. Virgin Islands.  
703-527-3887 – for calls originating elsewhere.  
(Collect calls accepted)

---

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

<u>Chemical Name</u>	<u>CAS No.</u>	<u>%Range</u>	<u>Trade Secret</u>
Napthenic Petroleum Distillate	64742-52-5	60.0 – 100.0	
Zinc Compounds	Proprietary	<0.3	

---

**3. HAZARDS IDENTIFICATION**

**Emergency Overview**

Harmful if Swallowed. Eye and Skin irritant

**OSHA Regulatory Status**

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product.

**Potential Health Effects**

**Route(s) of Entry:**

Absorption, Inhalation, and Ingestion.

**Health Hazards (Acute and Chronic):**

See signs and symptoms below

Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR

**Signs and Symptoms:**

Eye Contact: May cause slight irritation  
Skin Contact: May cause slight irritation  
Inhalation: If oil mist is inhaled for prolonged periods, may cause irritation.  
Ingestion: Can be Harmful or fatal if swallowed.

**Medical Conditions generally Aggravated by Exposure:**

None known

**Other Health Warnings:**

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

**Potential Environmental Effects**

Not Available

---

**4. FIRST AID MEASURES**

**Emergency and First Aid Procedures:**

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids and get prompt medical attention.  
Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.  
Inhalation: Remove to fresh air. If breathing becomes difficult, get prompt medical attention.  
Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

**Note to Physicians:**

N/D

---

**5. FIRE FIGHTING MEASURES**

**Suitable Extinguishing Media:**

Water Fog, Foam, Carbon Dioxide, Dry Chemical

**Unsuitable Extinguishing Media:**

Do not use forced water stream as this could cause the fire to spread.

**Products of Combustion:**

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, phosphorus, nitrogen and sulfur oxides.

Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR

**Protection of Firefighters:**

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently.

---

**6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions:**

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

**Environmental Precautions:**

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

**Methods for Containment:**

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

**Methods for Cleanup:**

Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using a vacuum to recover material.

**Other Information:**

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred.

---

**7. HANDLING AND STORAGE**

**Handling Precautions:**

Handling: Use with adequate ventilation and proper protective equipment. Do not use or store near fire, sparks, or flame. Store containers below 120°F.

**Storage Precautions:**

Keep container closed tightly when not in use. Store in cool place away from oxidizing agents.

Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Chemical Name</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Other Limits</u>
Zinc Compounds	N/E	N/E	Not Available
Naphthenic Petroleum Distillate	5 mg/m3	5 mg/m3	Not Available

### Exposure Controls:

See above applicable exposure limits. Maintain adequate ventilation. Avoid breathing mist. In restricted areas, use approved chemical filters designed to remove mist. In confined areas, use approved air line type respirator or hood. A self-contained breathing apparatus is required for vapor or mist concentrations above TLV limit.

### Personal Protective Equipment:

For prolonged exposure wear protective safety glasses, gloves, and apron.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Boiling Point:</b> 465°F	<b>Melting Point:</b> N/A
<b>Boiling Range:</b> Not Available	<b>Freezing Point:</b> Not Available
<b>Solubility in Water:</b> Insoluble	<b>Evaporation Rate (Butyl Acetate = 1):</b> Slow
<b>Flash Point:</b> 320°F	<b>Flash Point Method:</b> COC
<b>Odor Threshold:</b> Not Available	<b>Appearance and Odor:</b> Clear amber oil with petroleum odor
<b>Vapor Density (AIR=1):</b> 4.3	<b>Vapor Pressure (mm Hg):</b> 0.008
<b>pH Range:</b> N/A	<b>Partition Coefficient:</b> Not Available
<b>Decomposition Temp:</b> Not Available	<b>Auto-Ignition Temp:</b> Not Available
<b>Lower Explosive Limit:</b> N/D	<b>Upper Explosive Limit:</b> N/D
<b>Specific Gravity (H<sub>2</sub>O=1):</b> .90	
<b>Other Information:</b> N/D	

---

## 10. STABILITY AND REACTIVITY

### Stability:

Stable

### Conditions to Avoid:

See incompatible materials below

### Incompatible Materials:

Avoid contact with strong oxidizing agents

### Hazardous Decomposition Products:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, phosphorus, nitrogen and sulfur oxides.

**Material Safety Data Sheet**

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

**Possibility of Hazardous Reactions:**

Will not occur

---

**11. TOXICOLOGICAL INFORMATION**

N/D

---

**12. ECOLOGICAL INFORMATION**

N/D

---

**13. DISPOSAL CONSIDERATIONS**

DISPOSAL: This container may be recycled in a recycling center when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

---

**14. TRANSPORT INFORMATION**

**Shipping Name:** Not Available

**DOT Hazard Class:** Not Available

**UN/NA#:** Not Available

**DOT Subsidiary Hazard Class:** Not Available

**Packing Group:** Not Available

**Transportation Information:**

DOT Shipping Name: Not DOT regulated.

DOT Hazard Class: None

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US): Not Regulated

International:

ICAO/IATA: Not Regulated

IMDG: Not Regulated

