

## Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

---

**1. MATERIAL AND COMPANY IDENTIFICATION**

**Material Name** : Super S Synblend 5w20 Motor Oil  
**Uses** : Motor Oil

**Manufacturer/Supplier** : Smitty's Supply, Inc  
 PO Box 530  
 Roseland, LA 70456  
 USA

**MSDS Request** : 985-748-9687

**Emergency Telephone Number** : 800-424-9300 – toll free in the U.S., Canada and  
**CHEMTREC** U.S. Virgin Islands.  
 703-527-3887 – for calls originating elsewhere.  
 (Collect calls accepted)

---

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

<u>Ingredients</u>	<u>CAS#</u>	<u>Concentration</u>
Synthetic Blend Motor Oil		
Highly refined petroleum oils	Mixture	60 – 90 % volume
Synthetic hydrocarbon base oil	Mixture	10 – 35 % volume
Proprietary additives (contains <1% zinc)	Mixture	1 – 5 % volume

---

**3. HAZARDS IDENTIFICATION****Emergency Overview**

**Appearance and Odor:** Pale liquid. Mild odor.

**Health Hazards:** No known immediate health hazards.

**Physical Hazards:** No known physical hazards.

**NFPA Rating (Health, Fire, Reactivity):** 0, 1, 0

Hazard Rating: Least – 0 Slight – 1 Moderate – 2 High – 3 Extreme - 4

**Route(s) of Exposure:** Skin

**Inhalation:** Inhalation of vapors (generated at high temperatures only) or oil mist may cause mild irritation of the nose, throat, and respiratory tract.

Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

**Eye Irritation:** Lubricating oils are generally considered no more than minimally irritating to the eyes.

**Skin Contact:** Lubricating oils are generally considered no more than minimally irritating to the skin. Prolonged and repeated contact may result in defatting and drying of the skin that may cause various skin disorders such as dermatitis, folliculitis or oil acne.

**Ingestion:** Lubricating oils are generally no more than slightly toxic if swallowed.

**Other Health Effects:** The International Agency for Research on Cancer (IARC) has determined there is sufficient evidence for the carcinogenicity in experimental animals of used gasoline motor oils. Handling procedures and safety precautions in the MSDS should be followed to minimize exposure to the used product.

**Signs and Symptoms:** Irritation as noted above.

**Aggravated Medical Conditions:** Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

**For additional health information, refer to section 11.**

---

#### 4. FIRST AID MEASURES

**Inhalation:** Remove victim to fresh air and provide oxygen if breathing is difficult. Get medical attention.

**Skin:** Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

**Eye:** Flush with water. If irritation occurs, get medical attention.

**Ingestion:** Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical attention.

**Note to Physician:** In general, emesis induction is unnecessary in high viscosity, low volatility products such as oils and greases.

---

## 5. FIRE FIGHTING MEASURES

**Flash Point (Method):** >400°F / >204.44°C (Cleveland Open Cup)

**Upper Flammability Limit:** Not Determined

**Lower Flammability Limit:** Not Determined

**Extinguishing Media:** This material is non-flammable. Material will float and can be re-ignited on surface of water. Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames. Do not use a direct stream of water.

**Fire Fighting Instructions:** Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus. This material is non-flammable.

**Unusual Fire Hazards:** Material may ignite when preheated.

---

## 6. ACCIDENTAL RELEASE MEASURES

**Protective Measures:** May burn although not readily ignitable. Dike and contain spill.

Wear appropriate personal protective equipment when cleaning up spills. Refer to Section 8.

**Spill Management:**

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage / salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

**Reporting:**

CERCLA: Product is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) petroleum exclusion. Releases to air, land, or water are not reportable under CERCLA (Superfund).

CWA: This product is an oil as defined under Section 311 of EPA's Clean Water Act (CWA). Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center, 1-800-424-8802.

## Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR

1910.1200

---

**7. HANDLING AND STORAGE****Precautionary Measures:**

Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet. Launder contaminated clothing before reuse. Properly dispose of contaminated leather articles such as shoes or belts that cannot be decontaminated. Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking.

**Storage:**

Do not store in open or unlabeled containers. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

**Container Warnings:** Keep containers closed when not in use. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Chemical	Limit	TWA	STEL	Ceiling	Notation
Oil Mist, mineral	ACGIH TLV	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>		
Oil Mist, mineral	OSHA PEL	5 mg/m <sup>3</sup>			
Polyalphaolefin	ACGIH TLV	5 mg/ m <sup>3</sup>	10 mg/m <sup>3</sup>		
Polyalphaolefin	OSHA PEL	5 mg/m <sup>3</sup>			

**Exposure Controls:**

Provide adequate ventilation to control airborne concentrations below the exposure guidelines / limits.

**Personal Protection:**

Personal protective equipment (PPE) selections vary based on potential exposure conditions such as handling practices, concentration and ventilation. Information on the selection of eye, skin, and respiratory protection for use with this material is provided below.

**Eye Protection:**

Chemical Goggles, or Safety glasses with side shields.

**Skin Protection:**

Use protective clothing which is chemically resistant to this material. Selection of protective clothing depends on potential exposure conditions and may include gloves, boots, suits and other items. The selection(s) should take into account such factors as job task, type of exposure and durability requirements.

**Material Safety Data Sheet**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Published literature, test data and/or glove and clothing manufacturers indicate the best protection is provided by: Neoprene, or Nitrile Rubber

**Respiratory Protection:**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Types of respirator(s) to be considered in the selection process include:

For Mist: Air Purifying, R or P style NIOSH approved respirator.

For Vapors: Air Purifying, R or P style prefilter & organic cartridge, NIOSH approved respirator. Self-contained breathing apparatus for use in environments with unknown concentrations or emergency situations.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance & Odor:** Pale liquid. Mild odor.

**Substance Chemical Family:** Lubricants

**Physical State:** Liquid

<b>Flash Point</b>	>400°F (Cleveland Open Cup)	<b>Pour Point</b>	-45°F
<b>Specific Gravity</b>	0.86 – 0.88	<b>Viscosity</b>	25 cST – 75cST @ 40°C

**Odor Threshold:** Not Determined

**Partition Coefficient:** Not Determined

**pH:** Not Determined

---

**10. REACTIVITY AND STABILITY**

**Stability:** Material is stable under normal conditions.

**Conditions to Avoid:** Avoid heat and open flames.

**Materials To Avoid:** Avoid contact with strong oxidizing agents.

## Material Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

**Hazardous Decomposition Products:** Thermal decomposition products are highly dependent on combustion conditions. A complex mixture of airborne solids, liquids and gases will evolve when this material undergoes pyrolysis or combustion. Aldehydes, Carbon Monoxide, Carbon Dioxide, Ketones and other unidentified organic compounds may be formed upon combustion.

---

**11. TOXICOLOGICAL INFORMATION****Acute Toxicity**

TEST	Result	OSHA Classification	Material Tested
Dermal LD50	>5.0g/kg (Rabbit)	Non-Toxic	Based on components(s)
Oral LD50	>5.0g/kg (Rat)	Non-Toxic	Based on components(s)

**Carcinogenicity Classification**

Chemical Name	NTP	IARC	ACGIH	OSHA
Synthetic Blend Motor Oil	No	No	No	No

---

**12. ECOLOGICAL INFORMATION****Environmental Impact Summary:**

There is no ecological data available for this product. However, this product is an oil. It is persistent and does not readily biodegrade. However, it does not bioaccumulate.

---

**13. DISPOSAL CONSIDERATIONS****RCRA Information:**

Under RCRA, it is the responsibility of the user of the material to determine, at the time of the disposal, whether the material meets RCRA criteria for hazardous waste. This is because material uses, transformations, mixtures, processes, etc. may affect the classification. Refer to the latest EPA, state and local regulations regarding proper disposal.

---

**14. TRANSPORT INFORMATION****US Department of Transportation Classification**

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

**Oil:** This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures solutions containing 10% or more of this product may also be subject to this rule.

**International Air Transport Association**

Not regulated under IATA rules.

**International Maritime Organization Classification**

Not regulated under International Maritime Organization rules.

---

**15. REGULATORY INFORMATION**

<b>Federal Regulatory Status</b>
----------------------------------

**OSHA Classification:**

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**WHMIS Classification:** Not a controlled substance.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**Ozone Depleting Substances (40 CFR 82 Clean Air Act):**

This material does not contain nor was it directly manufactured with any Class I or Class II ozone depleting substances.

**Superfund Amendment & Reauthorization Act (SARA) Title III:**

There are no components in this product on the SARA 302 list.

**SARA Hazard Categories (311/312):**

Immediate Health	Delayed Health	Fire	Pressure	Reactivity
NO	NO	NO	NO	NO

**SARA Toxic Release Inventory (TRI) (313):**

There are no components in this product on the SARA 313 list.

**Material Safety Data Sheet**

**Toxic Substances Control Act (TSCA) Status:**

All component(s) of this material is (are) listed on the EPA/TSCA Inventory of Chemical Substances.

**Other Chemical Inventories:**

Component(s) of this material is (are) listed on the Australian AICS, Canadian DSL, Chinese Inventory, European EINECS, Korean Inventory.

<b>State Regulation</b>
-------------------------

This material is not regulated by California Prop 65, New Jersey Right-to-Know Chemical List or Pennsylvania Right-To-Know Chemical List. However, for details on your regulation requirements you should contact the appropriate agency in your state.

---

**16. OTHER INFORMATION**

NFPA RATING (HEALTH, FIRE, REACTIVITY) : 0, 1, 0

**MSDS Version Number** : 2.0

**MSDS Effective Date** : 09/08/2009

**MSDS Revisions** : A vertical bar (|) in the left margin indicates an amendment from the previous version.

**MSDS Regulation** : The content and format of this MSDS is in accordance with the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**MSDS Distribution** : The information in this document should be made available to all who may handle the product.

**Disclaimer** : The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product.