

# Super S<sup>®</sup> Multipurpose D/M ATF

## TECHNICAL PRODUCT INFORMATION



### **Super S Multipurpose D/M ATF**

**Super S Multipurpose D/M ATF** is a high performance formulation of base oils and a sophisticated additive package designed for most late model year vehicles, both foreign and US made.

**Super S Multipurpose D/M ATF** meets GM Dexron III specification, and may be used in applications calling for Dexron III G, Dexron IIE, Dexron II, Dexron, Mercon, or Type A Suffix A transmission fluid.

### FEATURES/ BENEFITS

- **Inventory consolidation**- one product can serve most automatic transmission applications.
- **Excellent all-temperature, year-round protection and performance** - **Super S Multipurpose D/M ATF** remains fluid at low temperatures for cold weather shifting and to eliminate premature wear (especially at start-up) and maintains its properties at high temperatures and under extreme loads and operating conditions.
- **Proven anti-wear protection and shear stability** - **Super S Multipurpose D/M ATF** will help to extend the life and service intervals of your transmission, especially for transmissions experiencing more startup and/or shift cycles, or extreme loads or environments.
- **Smoother shifting, protects against shudder** - The proven additive technologies combine to provide smoother, more consistent shifting performance and provide smooth, positive lockup, reducing shudder.
- **Extended service life and performance** - **Super S Multipurpose D/M ATF** resists oxidation, retains frictional performance, and protects against rust and corrosion.

**Super S Multipurpose D/M ATF** is designed for use in:

- Passenger cars • Light and Heavy Duty Trucks • Commercial Vehicles and Trucks
- On/Off Highway Vehicles • Buses and Coaches • Emergency Vehicles
- Any automatic transmissions manufactured around the world calling for Dexron or Mercon ATF
- May also be used in power steering units and hydraulic system
- Not for use in CVT (Continuously Variable Transmissions) or DCT (Dual Clutch Transmissions) which require specialized fluids.

### RECOMMENDATIONS/SPECIFICATIONS

**Super S Multipurpose D/M ATF** is suitable for use in the vehicles that specify the following requirements:

- GM DEXRON<sup>®</sup>, DEXRON<sup>®</sup> II, II-E, III, III-G, III-H
- Ford MERCON<sup>®</sup>
- Chrysler (Mopar) ATF-Plus,
- CAT TO-2
- BMW • Honda/ Acura • Hyundai • JASO • Mercedes • Mitsubishi
- Nissan/ Infinity Matic • Toyota/ Lexus T-(II, III) • Volvo • VW

*ATF recommendations may vary between models from a manufacturer*

*Consult owners manual for the correct fluid recommendation*

### SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling as for any petroleum product.

**TYPICAL CHARACTERISTICS**

<b>Super S<sup>®</sup> Multipurpose D/M ATF</b>		
<i>Properties</i>	<i>Test Method ASTM D-</i>	<i>Typical Results</i>
API Gravity	1298	33
Appearance	Visual	Red
Flash Point, COC °C/°F	92	185 /365
Pour Point, °C/°F	97	-48/-54
Viscosity cSt @ 40°C cSt @ 100°C	445	32.8 7.2
VI	2270	192
Brookfield Viscosity, cP @ -40°C	2983	17500

Typical test data are average values only.  
 Minor variations which do not affect product performance are to be expected during normal manufacturing.

**PRODUCT NUMBERS**

- SUS 26            12/1 quart bottles
- SUS 126         6/1 gallon bottles
- SUS 126-3      3/1 gallon bottles
- SUS 6            5 gallon pail
- SUS 44          55 gallon drum
- SUS 44Bulk     Bulk
- SUS 44BD      Bulk/Drum
- SUS 44 Tote    275 gallon Tote