

Super S[®] Chain Oil - No Tack

TECHNICAL PRODUCT INFORMATION



Super S Chain Oil - No Tack

Super S Chain Oil - No Tack is formulated with virgin mineral oil and specific additives for today's high speed chain saws. Contains no tackifier

FEATURES/ BENEFITS

- Formulated with high quality base oils and a balanced additive package
- Different base oil viscosities: summer and winter
- Contains no tackifier
- EP (extreme pressure) additives lubricate under heavy load and shock load conditions
- Penetrates the chain: provides start up lubrication
- Resists wear in service
- Resists corrosion in storage

APPLICATIONS

- **Super S Bar and Chain Oil** is designed for use in:
 - Residential, commercial and industrial chain saws
 - Hand operated and automatic oilers
 - Adverse operating conditions of the forest products industry
 - Chains, bars, and sprockets

RECOMMENDATIONS/SPECIFICATIONS

- All types of chain saws

SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling as for any petroleum product.

TYPICAL CHARACTERISTICS

Super S Chain Oil - No Tack			
Properties	Test Method ASTM D-	Data	
		Summer	Winter
Gravity, °API	1298		
Flash Point °C/°F,	92	218/425	210/410
Pour Point °C/°F	97	-24/-10	-29/-20
Color	1500	4	4
Viscosity SUS @ 100°F	88	630	300

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS 191 55 gallon drum
SUS 191bulk Bulk