

Super S[®] R & O Hydraulic Oil

TECHNICAL PRODUCT INFORMATION



Super S R & O Hydraulic Oil

Super S R & O Hydraulic Oil is blended from highly-refined base stocks to provide outstanding lubricating properties in a wide-range of applications. It is formulated with select additives to provide excellent anti-rust, anti-oxidation, anti-corrosion and anti-foam performance.

FEATURES/ BENEFITS

Super S R & O Hydraulic Oil

- Protection against oxidation
- Protection against rust and corrosion
- Low foaming

APPLICATIONS

Super S R & O Hydraulic Oil is suitable for use in the following applications:

- Applications where a straight mineral oil is required without extreme pressure (EP), detergent, dispersant or anti-wear additives.
- General machine oil
- Low pressure circulating fluid
- Non-Critical hydraulic applications
- Air-tool oil
- Drip or splash lubricant
- Spindle Oil
- Lubrication of light-duty compressors

SPECIAL HANDLING, NOTICES OR WARNINGS

Handle as you would any petroleum product

TYPICAL CHARACTERISTICS

Super S R & O Hydraulic Oil			
Properties	Test Method ASTM-D	32	68
Specific Gravity		0.8944	0.8871
Gravity, API, 60°F	1298	26.0	28.0
Pour Point, °F	97	-10	-20
Flash Point, COC, °F	92	390+	400+
Viscosity			
cSt @ 40 °C	445	30 - 42	68
cSt @ 100 °C	445	5.7	6.9
SUS @ 100 °F	88	150	315
Approximate ISO		32	68
Approximate SAE		10	20

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

ISO 32

SUS 23 6/1 gallon bottles
SUS 1 5 gallon pail
SUS 3 55 gallon drum
SUS 3Bulk Bulk

ISO 68

SUS 2 5 gallon pail
SUS 2-55 55 gallon drum

Super S Lubricants

July 16, 2010

