

Super S® ATF+4 Automatic Transmission Fluid



TECHNICAL PRODUCT INFORMATION

Super S ATF+4 Automatic Transmission Fluid

Super S ATF+4 is an Automatic Transmission Fluid developed for use in all Chrysler automatic transmissions.

FEATURES/ BENEFITS

Super S ATF+4 offers the following advantages:

- Warranty coverage: approved by Chrysler Fluids group for all Chrysler transmissions
- Correct flow and frictional properties:
- Ensures smooth operation in Chrysler equipment
- Remains fluid at low temperatures for cold weather shifting and to eliminate premature wear (especially at start-up)
- Maintains its properties at high temperatures and under extreme loads and operating conditions
- Extended service life and performance - sheer stable viscosity modifiers and additive that resist oxidation, retain frictional performance, and protects against rust and corrosion.

APPLICATIONS

Super S ATF+4 is designed for use in:

- All Chrysler automatic transmissions
- Any other application where ATF+4 is recommended
- Not for use in CVT (Continuously Variable Transmissions) or DCT (Dual Clutch Transmissions) which require specialized fluids.
- Not recommended in transmissions calling for DEXRON® or MERCON® fluids

RECOMMENDATIONS/SPECIFICATIONS

Super S ATF+ is suitable for use in the vehicles that specify the following requirements:

- Chrysler ATF+4(MS 9602) ATF+3(MS7176-E)
- Chrysler (Mopar) ATF-Plus

SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling as for any petroleum product.

TYPICAL CHARACTERISTICS

Super S® ATF+4		
Properties	Test Method ASTM D-	Typical Results
API Gravity	1298	32
Appearance	Visual	Red
Flash Point, COC °C/°F	92	204° C /400°F
Pour Point, °C/°F	97	-34° C -30°F
Viscosity cSt @ 40°C cSt @ 100°C	445	36.0 7.55
VI	2270	185
Brookfield Viscosity @ -40°C cP	2983	13,000

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS 224 12/1 quart bottles SUS 224-55BD Bulk/Drum
SUS 224-55 55 gallon drum