



# SuperSyn® Premium Full Synthetic CVT Fluid

**SuperSyn® Premium Full Synthetic CVT Fluid** is a full synthetic transmission fluid combined with a highly sophisticated additive package specially formulated to provide robust protection for the steel components in vehicles equipped with either chain or push belt continuously variable transmissions. This fluid is suitable for use as a service fill fluid for all chain or belt driven CVT's coupled with engine displacement sizes 3.5 liters or less.

**SuperSyn® Premium Full Synthetic CVT Fluid's** strong oil film and sheer stability provides optimum protection against shudder commonly associated with CVT transmissions. Extends belt, chain, and pulley life by placing a film layer between the metal-to-metal contact points that cause wear. New, unique formula has excellent thermal and oxidation stability providing you more protection for more miles than ever before.

The long life friction modifiers found in **SuperSyn® CVT** along with highly shear stable viscosity improver allow for longer drain intervals than other leading brands. These long-life modifiers also provide for the smooth, seamless shifts expected from sophisticated CVT's in late model cars. The robust film formed on internal gears provide excellent wear protection for reduced down time and maintenance costs.

## TYPICAL CHARACTERISTICS

SuperSyn Premium CVT	
Properties	Data
Appearance	Typical
Pour Point	-50°C
Flash Point	206°C
Viscosity @ 40°C	36.95 cSt
Viscosity @ 100 °C	7.5 cSt
Viscosity Index	176
Gravity, API	32.8
Brookfield -40°C	12,000

## FEATURES/BENEFITS

- Superior anti-shudder durability for enhanced driving comfort
- Balanced formulation for high torque capacity
- Superior Anti-Wear Protection to provide long service life
- Balanced formulation for high torque capacity
- Compatibility in multiple CVT transmission types
- Patented Technology designed to exceed performance requirements of the major Asian OEM's
- Longer life and service interval than leading competitors based on Vehicle Mileage Accumulation Test



**SuperSyn Premium Full Synthetic CVT Fluid** is suitable for the following manufacturers as long as the engine is 3.5l or less:

Audi Multitronic	Hyundai/Kia SP III (CVT model)	Subaru Lineartronic chain CVT and CVT II Fluid
BMW Mini Cooper EZL 799/799A	Idemitsu CVTS-EX1	Subaru Lineartronic High Torque (HT) CVT Fluid
Daihatsu AMMIX CVTF DFE	Mazda JWS 3320	Subaru NS-2
Daihatsu AMMIX CVT Fluid DC	Mini Cooper EZL 799/EZL 799A/ZF CVT V1	Suzuki CVTF TC
Daihatsu AMMIX CVT Fluid DFC	Mitsubishi CVTF-J1 (MMC Diaqueen CVT Fluid J1)	Suzuki CVTF 3320
Daihatsu Fluid TC	Mitsubishi CVTF-J4 and -J4+ (MMC Diaqueen CVT Fluid J4 and J4+)	Suzuki NS-2
Dodge/Jeep/Chrysler NS-2	Mitsubishi ( Diaqueen) SP-III (CVT model only)	Suzuki CVT Green 1 & 2
Dodge/Chrysler/Jeep/Mopar CVT+4	Nissan NS-1, -2, -3	Suzuki CVT Green 1V
GM/Saturn DEX-CVT	Punch CVT	Toyota CVTF TC
Honda HMMF (without starting clutch)	Shell Green 1V	Toyota CVTF FE
Honda HCF2	Subaru iCVT	VW/Audi TL 521 16 (G 052 516)
Honda Z-1 (CVT model, without starting clutch, not SFU for 2001-2007 Honda Fit & Jazz)	Subaru iCVT FG	
Hyundai/Kia CVT-J1	Subaru ECVT	