



# Super S<sup>®</sup> Multipurpose D/M ATF

**Super S<sup>®</sup> Multipurpose D/M ATF** is a high performance formulation of high viscosity index base oils and a sophisticated additive package designed for most late model year vehicles, both foreign and US made.

**Super S<sup>®</sup> Multipurpose D/M ATF** is a friction modified automatic transmission fluid which meets GM Dexron III specification, and may be used in applications calling for Dexron III G, Dexron IIE, Dexron II, Dexron, Mercon, or Type A Suffix A transmission fluid.

Dexron/Mercon III transmission fluids are characterized by their excellent low temperature performance along with an exceptionally high level of oxidative stability to maintain low temperature fluidity and resist high temperature oil degradation. This allows for extended drain intervals beyond previous Dex/Merc specifications. **Super S<sup>®</sup> MP D/M ATF** is blended to meet the stringent requirements of leading automotive transmission manufacturers and remains the most recommended fluid for service fill applications.

## FEATURES/ BENEFITS

- **Inventory consolidation**- one product can serve most automatic transmission applications.
- **Excellent all-temperature, year-round protection and performance** - **Super S<sup>®</sup> Multipurpose D/M ATF** remains fluid at low temperatures for cold weather shifting and to eliminate premature wear (especially at start-up) and maintains its properties at high temperatures and under extreme loads and operating conditions.
- **Proven anti-wear protection and shear stability** - **Super S<sup>®</sup> Multipurpose D/M ATF** will help to extend the life and service intervals of your transmission, especially for transmissions experiencing more startup and/or shift cycles, or extreme loads or environments.
- **Smoother shifting, protects against shudder** - The proven additive technologies combine to provide smoother, more consistent shifting performance and provide smooth, positive lockup, reducing shudder.
- **Extended service life and performance** - **Super S<sup>®</sup> Multipurpose D/M ATF** resists oxidation, retains frictional performance, and protects against rust and corrosion.

**Super S<sup>®</sup> Multipurpose D/M ATF** is designed for use in:

- Passenger cars
- Light and Heavy Duty Trucks
- Commercial Vehicles and Trucks
- On/Off Highway Vehicles
- Buses and Coaches
- Emergency Vehicles
- Any automatic transmissions manufactured around the world calling for GM Dexron<sup>®</sup> III, Ford Mercon<sup>®</sup>, or Allison C-4 fluids. Do not use where GM Dexron<sup>®</sup> VI, Ford Mercon<sup>®</sup> V, Mercon<sup>®</sup> LV, or Mercon<sup>®</sup> SP fluids are required.
- May also be used in power steering units and hydraulic system
- Not for use in CVT (Continuously Variable Transmissions) or DCT (Dual Clutch Transmissions) which require use of specialized fluids.

## RECOMMENDATIONS/SPECIFICATIONS

**Super S Multipurpose D/M ATF** is suitable for use in vehicles that specify the following requirements:

- GM DEXRON<sup>®</sup>, DEXRON<sup>®</sup> II, II-E, III, III-G, III-H
- Ford MERCON<sup>®</sup>
- Chrysler (Mopar) ATF-Plus,
- CAT TO-2
- Hyundai
- Toyota/ Lexus T-(II, III)
- JASO
- Honda/ Acura
- BMW
- Nissan/ Infinity Matic
- Mercedes
- Volvo
- Mitsubishi
- VW

*ATF recommendations may vary between models from a manufacturer Consult owners manual for the correct fluid recommendation*

## SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling as for any petroleum product.

**Typical Characteristics**

<b>SUPER S® MULTIPURPOSE D/M ATF</b>		
<i>Properties</i>	<i>Test Method ASTM D-</i>	<i>Typical Results</i>
API Gravity	1298	33
Appearance	Visual	Red
Flash Point, COC °C/°F	92	185 /365
Pour Point, °C/°F	97	-48/-54
Viscosity cSt @ 40°C cSt @ 100°C	445	32.8 7.2
VI	2270	192
Brookfield Viscosity, cP @ -40°C	2983	17500
Foam Test	892	100/0 100/0 100/0 100/0
Rust and Corrosion	665	None
Copper Strip	130	1a

Typical test data are average values only.  
 Minor variations which do not affect product performance are to be expected during normal manufacturing.

**Product Numbers**

- SUS 26            12/1 quart bottles
- SUS 126         6/1 gallon bottles
- SUS 126-3      3/1 gallon bottles
- SUS 6            5 gallon pail
- SUS 44          55 gallon drum
- SUS 44Bulk     Bulk
- SUS 44BD      Bulk/Drum
- SUS 44 Tote    275 gallonTote