

# Super S<sup>®</sup> Cotton Picker Spindle Cleaner

## TECHNICAL PRODUCT INFORMATION



### **Super S Cotton Picker Spindle Cleaner**

**Super S Cotton Picker Spindle Cleaner** is a water soluble oil-based liquid that mixes well with water of any hardness and cleans dirt, plant materials, and other foreign contaminants from cotton picker spindles. Non-staining, non-flammable formula improves yield and helps keep equipment running longer. Mixes with all hardness' of water for use in any operational environment.

#### **FEATURES/ BENEFITS**

- Mixes well with all water hardness
- Non flammable when mixed with water
- Keeps spindles cleaner
- Reduces Wrapping
- Reduces Staining
- Higher yield of cleaner cotton

#### **DIRECTIONS**

1. Clean moistener system of wetting agents and cleaners, fill moistener tank 1/2 of water. WATER AND CLEANER DO NOT MIX IF WATER POURED INTO CLEANER.
2. Agitate the water by operating the moistener control water system. This recirculate the water back to the supply tank.
3. While water is agitating, slowly add the spindle cleaner to the water at a ratio of one gallon of cleaner to 64 gallons of water.
4. Finish filling the tank with water while agitating. Agitate for and additional 5 minutes

#### **SPECIAL HANDLING, NOTICES OR WARNINGS**

##### **NOTE:**

For best results the mixture should be used within 24 hours. If mixture is allowed to stand for extended time, agitate for several minutes before picking. Additional cleaner can be added for make up in a tank already containing some previous mixture. If tank is less than half full, fill with plain water to half full. Follow mixing directions and add cleaner at the correct ratio for the amount of water being added for make up.

##### **STORAGE:**

Drums and pails of spindle cleaner concentrate should be stored to avoid contamination with water. If water gets into the drum or pail, it will cause curdling. If necessary to store outside, place drums on side with bungs at 3 and 9 o'clock position.

**TYPICAL CHARACTERISTICS**

<b>Super S Cotton Picker Spindle Cleaner</b>		
<i>Property</i>	<i>Test Method ASTM -D</i>	<i>Typical Properties</i>
Specific Gravity	4052	1.002
Flash Point °C/ °F	92	148/300
Fire Point °C/ °F	92	177/350
Pour Point °C/ °F	97	-17.8/0
Viscosity cSt @ 40°C SUS @ 40°C	445	22.0 108.4
Color	1500	2

Typical test data are average values only.  
 Minor variations which do not affect product performance are to be expected during normal manufacturing.