



## **Super S® GL-5 85W-140 Gear Oil with Red Tack**

**Super S® GL-5 85W-140 Gear Oil with Red Tack** is a sulphur-phosphorus, heavy duty extreme pressure (EP) gear lubricant formulated for use in automobiles, trucks, heavy duty differentials, farm, and construction equipment that call for an API GL-5 type product. Formulated from high VI paraffin base oil with a legacy additive package which is further fortified with a tackiness agent which provides excellent adhesion to gear sets.

**Super S® 85W-140 Red Tack** provides excellent water resistance and is very shear stable maximizing load carrying capabilities. Proprietary friction modifiers provide a smoother ride increasing fuel mileage by as much as 4% over GL-4 rated products. While oxidation and rust inhibitors ensure you're protected up to 2 yrs / 250,000 miles.

### **FEATURES/ BENEFITS**

- **Formulated with Sulfur-Phosphorus EP additives** to provide anti-wear and anti- scuff performance
- **High Film Strength & Shear Stability** which ensures retention of viscosity to protect equipment against metal-to-metal contact and wear, especially in higher temperatures

- **Formulated with No Zinc** complying with most manufacturers' requirements for truck driving axles
- **Excellent Extreme Temperature Properties** promotes oil flow to help protect gears & bearings even at sub-zero temperatures while maintaining lubricity through extreme heat
- **Includes Rust, Oxidation & Corrosion Inhibitors** that resist degradation and sludging for longer oil life (up to 2 yr/250,000 miles) with fewer change-outs and better protection of gears
- **Tackiness Agent** provides excellent adhesion ensuring maximum protection in heavily loaded gear sets
- **Distinct Red Color** for easy identification & leak detection

### **APPLICATIONS/RECOMMENDATIONS**

- Mack GO-J, GO-H, GO-G
- Hypoid/Worm Gears calling 85W-140 gear oil
- Differentials and conventional transmissions in passenger cars and trucks where GL-5 type lubricant is specified

### **SPECIFICATIONS**

- API GL-5, MT-1
- SAE 2360 (formerly MIL-PRF-2105E)

### **TYPICAL CHARACTERISTICS**

<i>Property</i>	<i>Test Method ASTM - D</i>	<i>SAE Grade</i>
		<b>85W-140</b>
Flash Point, CoC °C /°F	92	218/425
Pour Point, °C /°F	97	-12/-10
Viscosity, cSt @ 100°C	445	26.0
Viscosity Index	2270	100
Viscosity cp @ °C	2983	12000 @ -12C