



### Super S Premium Universal Tractor Hydraulic

**Fluid** is a premium multi-functional fluid used as a hydraulic medium and as a transmission, differential, power steering, power brake, power take-off (PTO), and implement drive fluid in equipment employing a common fluid reservoir. It meets or exceeds John Deere J20C performance specifications and is suitable for most applications calling for a universal tractor hydraulic fluid.

### Benefits

- **Responsive Performance** – maintains viscosity over wide temperature range to maximize performance
- **Extends Equipment Life** – reduces wear below J20C performance requirements for extended product life
- **Simplified Logistics** – one fluid for hydraulic, differential, PTO, power brake, power steering, etc

### Features

- Superior detergent/dispersant package keeps system cleaner for longer life
- Lubricates the transmission, differential and final drive gears in tractors
- Provides extreme pressure (EP) and anti-wear protection
- Protects against rust, corrosion, foaming and oxidation
- Prevents seal and pump deterioration
- Protects tractor transmission, axles and hydraulic pumps
- Eliminates brake chatter
- Controlled frictional characteristics permit the wet brakes to hold properly and allows smooth engagement of power take-off (PTO) clutches

### Applications

**Super S Premium Universal Tractor Hydraulic Fluid** has been field-tested and meets or exceeds where the following fluids are recommended:

Allis Chalmers PF-821XL

Allison C-4, C-3

Caterpillar TO-2

Denison HF-O

Deutz HTF

Ford /New Holland

M2C41-B, M2C48-B

M2C53-C, M2C77-A

M2C86-B, ESN-M2C134

M2C134-B, M2C134-C

M2C134-D

Harvester

Hy-Tran, spec. B-6

JI Case/David Brown

144, 145, 185

MS-1204, 1205

MS-1206 (Powergard PTF) MS-1209,

MS-1210 (TCH)

John Deere

J20, J20A (Hy-Gard)

J20C, J14B, J14C, J21A

303, Quatrol

CNH MAT 3525 / 3526 /3540

Massey Ferguson

M-1110, M-1127, M-1145

M-1129 (Permatran)

M-1135, Permatran III

Kubota UDT / Super UDT

Oliver Type 55

Renk Doromat ATF International

Steiger Hydraulic Trans Fluid

Sunstrand HMS-103

Versatile Gear/Hydraulic Trans Fluid JIC-143,

White Q1722, Q1826



**Typical Characteristics**

<b>Super S® Premium Universal Tractor Hydraulic Fluid</b>		
<i>Properties</i>	<i>Test Method ASTM D-</i>	<i>Data</i>
SAE Grade		10W-30
Flash Point °C/°F,	92	204/400
Pour Point °C/°F,	97	-29/-20
Color	1500	4.0 max
Viscosity	445	
cSt @ 40°C		53
cSt @ 100°C		9.2
Viscosity Index	2270	135

Typical test data are average values only.  
 Minor variations which do not affect product performance are to be expected during normal manufacturing.

**Product numbers**

SUS 236	5 gallon pail
SUS 236-55	55 Gallon drum
SUS 236tote	275 gal. tote
SUS 237bulk	Bulk

**Special handling, notices or warnings**

Use the same care and handling as with any petroleum product.