



## Super S® 15W-40 Low Ash Extended Drain Engine Oil

**Super S® NGEO 15W-40 Engine Oil** is a low ash, extended drain heavy duty engine oil designed for use in natural gas applications requiring **Cummins CES20085, Detroit Diesel 93K216, Volvo CNG, MB 226.9** or **Renault RGD** quality levels. **Super S® 15W-40 Low Ash Engine Oil** is formulated with premium high quality Group II base oils and state of the art additives to produce a high quality finished product that provides superior engine protection and cleanliness.

**Super S® 15W-40 Low Ash Engine Oil** provides a uniquely balanced premium formulation that minimizes ash deposits, oxidation, nitrification, valve regression and engine wear. **Super S® 15W-40 Low Ash Engine Oil** is recommended in mobile applications where diesel, compressed natural gas (CNG), liquid natural gas (LNG) or propane is used.

**Super S® 15W-40 Low Ash Engine Oil** is recommended for use with spark or direct ignitions in bus, delivery and service truck fleets, and also meets mobile gas engine performance requirements for **Cummins B1, C1, G5.9, G8.3, L Gas Plus, and ISL G series gas engines as well as Detroit Diesel Series gas engines**. May also be recommended for Mack, Isuzu, Hino, Hyundai, Freightliner, Kenworth, Navistar, Phoenix, and Westport applications for superb engine cleanliness and extended service operation.

### FEATURES

- Outstanding resistance against Oxidation and Nitration
- Extended drain capabilities to 1200 hrs in CNG/LNG engines
- Excellent wear protection
- Superb engine cleanliness and sludge control
- Minimizes ash deposits and valve regression
- Broad application range suitable for large fleets to include buses
- Reduced downtime and maintenance costs
- Excellent TBN retention beyond 1500 hrs
- Piston deposit control is better than diesel engine oils used in CNG engines
- Greatly reduces spark plug fouling

### APPLICATIONS

Suitable in trucks or buses requiring a **API CF-4** engine oil or where CNG/LPG are used.

**DETROIT DIESEL** DD93K216

**MERCEDES-BENZ** MB 226.9

**RENAULT** RGD

**VOLVO** CNG

**CUMMINS** CES20085, and B1, C1, G5.9, G8.3, L Gas Plus, and ISL G series



## Super S<sup>®</sup> 15W-40 Low Ash Extended Drain Engine Oil

---

### Typical Characteristics

<b>Product Code</b>	209
<b>Specific Gravity</b>	0.85
<b>Viscosity, cSt @ 40°C</b>	111
<b>Viscosity, cSt @ 100°C</b>	15.5
<b>Viscosity Index</b>	146
<b>Pour Point, °C</b>	-32
<b>Flash Point, °C</b>	231
<b>Base Number</b>	6.4
<b>Sulfated Ash %</b>	0.9

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.