



Super S[®] Premium Power Steering Fluid

Super S[®] Premium Power Steering Fluid is a premium quality fluid carefully blended from synthetic base stocks and select additives for use in select General Motors, Ford, Chrysler, and select Import power steering systems. It protects against wear, oxidation and corrosion and can be used for complete fluid replacement or as a top off in passenger cars and light trucks.

Super S[®] Premium Power Steering Fluid helps maintain efficiency, performance and the condition of power steering units. **Super S[®] Premium Power Steering Fluid** contains a unique friction modifier additive that has been shown to reduce power steering pump noise (squeal).

FEATURES/ BENEFITS

- Formulated with high quality base oils and a balanced additive package
- Compatible with most power steering fluids
- Suitable for systems requiring a Dexron/Mercon III type fluid
- Maintains system efficiency by keeping pump cooler than competing fluids
- Controls leaks and squeals
- Resists oxidation, corrosion, and wear
- Inhibits foaming

APPLICATIONS

- For use in automobiles and light trucks calling for D/M III or other ATF type Power Steering Fluid

TYPICAL CHARACTERISTICS

Super S [®] Premium Power	
Properties	Data
Gravity, °API	23.2
Flash Point °C/°F,	171/340
Density (lb/gal)	7.47
Color	1.5
Viscosity	
cSt @ 40°C	30.75
cSt @ 100°C	7.05

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing

Suitable for Use Applications
Audi P/N G002000
Chrysler MS 1872
Chrysler MS 5931F, P/N 04883077
Chrysler MS 9602, ATF+4
Ford M2C128-C and D
Ford M2C138-CJ
Ford M2C33-F
GM 9985010 Saginaw Power Steering System
GM 9985835 Wide Temperature Performance
GM P/N 89021184
Hyundai PSF-3
Kia PSF-3
Mercedes Benz 236.3 P/N 000 989 8803
Mitsubishi Diamond SP III
Mitsubishi PS Fluid
Nissan PSF-II
Pentosin CHF 7.1
Saab P/N (45) 30 09 800
Subaru P/N K0209A0080
Toyota PSF type EH, P/N 008886-01
VW P/N G002000

SPECIAL HANDLING, NOTICES OR WARNINGS

Handle as you would any petroleum product