



Super S® RV & Marine Antifreeze is formulated to winterize all types of potable water systems including recreational vehicles, trailers, swimming pool and spa equipment, boats, and vacation homes. Containing components considered GRAS (Generally Regarded as Safe), it is biodegradable, non-toxic, non-corrosive, and non-staining when used as directed.

Super S® RV & Marine Antifreeze provides burst protection to -50°F and is safe for use with brass, metal, copper, and plastic (except acetate) making it an excellent general purpose antifreeze. The ready-to-use, full strength formula includes Propylene Glycol improving customer safety and performance when compared to Ethylene Glycol based products. Propylene glycol is considered safe for incidental contact with people, pets, and wildlife. Not for use in radiators of gasoline, diesel, marine engines, boiler systems, nor solar collectors. Misapplication can cause severe damage to equipment.

Applications

- Potable Water Plumbing Systems
- Recreational vehicle plumbing systems
- Marine plumbing Systems
- Swimming Pool and Spa Equipment
- Vacation Home Plumbing Systems
- Most other potable water systems

Features

- Burst protection to -50°F (crystallization may occur around -20F, but pipes will not burst)
- Ready to use, no mixing required
- Safe, non-toxic, non-staining when used correctly
- Wide application range
- Broad range of applications
- Safe with brass, metal, copper, and plastic pipes excluding acetate

Typical Characteristics

Super S® RV & Marine Antifreeze	
Properties	
Appearance	Pink
pH	8.50
Freeze Point, °F	-20
Burst Protection, °F	-50
Specific Gravity @ 60F	0.995
Base Glycol	Propylene

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.



Special handling, notices or warnings

Use the same care and handling as with any synthetic motor oil.