

# Super S<sup>®</sup> Non-Detergent Motor Oil

## TECHNICAL PRODUCT INFORMATION



### **Super S Non-Detergent Motor Oil**

**Super S Non-Detergent Motor Oil** are blended from well refined petroleum base oils and may be used in older, worn engines with high oil consumption

#### **FEATURES/ BENEFITS**

- Well refined mineral oils with no added additives
- Available in 5 viscosity grades
- Mono grade formulations

#### **APPLICATIONS**

- Engines calling for API SA or SB performance level engine oils
- API GL-1 Gear Applications
- Older engines
- Engines with high oil consumption
- Non critical low pressure hydraulic systems
- Drip oilers, spindle lubrication, once thru applications
- Light duty compressors

#### **RECOMMENDATIONS/SPECIFICATIONS**

Recommended for applications calling for  
API SA, SB  
API GI-1

#### **SPECIAL HANDLING, NOTICES OR WARNINGS**

Use the same care and handling that you would use with petroleum products.

TYPICAL CHARACTERISTICS

Super S® Non-Detergent Motor Oil						
Property	Test Method ASTM -D	SAE Viscosity Grade				
		10	20	30	40	50
ISO VG Grade		32	68	100	150	220
API Gravity	1298	22.2	22.8	23.4	23.8	24.4
Pour Point °C/ °F	97	-23/-10	-21/-5	-21/-5	-15/5	-7/20
Viscosity , SSU @ 100°F	88	150	250	450	600	900
VI	2270	50	50	50	50	50

Typical test data are average values only.  
 Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

**SAE 10**

- SUS 84-3 3/1 gallon bottles
- SUS 84-1 6/1 gallon bottles
- SUS 7 5 gallon pail

**SAE 20**

- SUS 85 12/1 quart bottles
- SUS 85-55 55 gallon drum

**SAE 30**

- SUS 41 12/1 quart bottles
- SUS 10 5 gallon pail
- SUS 16 55 gallon drum
- SUS 41 Bulk

**SAE 40**

- SUS 45 12/1 quart bottles
- SUS 5405 6/5 quart bottles
- SUS 45-3 3/1 gallon bottles
- SUS 45-1 6/1 gallon bottles
- SUS 11 5 gallon pail
- SUS 11-55 55 gallon drum
- SUS 45Bulk Bulk

**SAE 50**

- SUS 86 12/1 quart bottles
- SUS 8605 6/5 quart bottles
- SUS 86-3 3/1 gallon bottles
- SUS 86-1 6/1 gallon bottles
- SUS 86-5 5 gallon pail
- SUS 86-55 55 gallon drum
- SUS 86Bulk Bulk