

Super S[®] 140 Solvent

TECHNICAL PRODUCT INFORMATION



Super S 140 Solvent

Super S Solvent 140 is a high flash solvent for general purpose cleaning.

FEATURES/ BENEFITS

With proper agitation in cleaning equipment, Super S Solvent 140 removes from metal surfaces:

- Grease
- Lubricating Oils
- Metal working fluids
- Fines
- Flash greater than 140 °F

APPLICATIONS

- Replace low flash solvent
- Compatible with most materials and plastics
- Use in a variety of parts cleaning equipment
- Contains NO hazardous substances (no TLV's, PEL's)

RECOMMENDATIONS/SPECIFICATIONS

- Super S 140 Solvent is NOT SARA (Superfund Amendments Reauthorization Act) reportable
- Less solvent monitoring and paperwork.
- Exceeds the VOC (Volatile Organic Compound) requirements of SCAQMD (South Coast Air Quality Management District) rule 1171 for use as a "Clean Air Solvent" in California.

SPECIAL HANDLING, NOTICES OR WARNINGS

Product contacting the eye may cause irritation. Prolonged or repeated skin exposure causes mild irritation, dermatitis and defatting.

TYPICAL CHARACTERISTICS

Super S 140 Solvent		
Property	Test Method ASTM -D	Data
Density(lb/gal)	1298	6.54
Flash Point °F	92	140
Viscosity cSt @ 40°C	445	1.7

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

- SUS 188 5 gallon pail
- SUS 189 55 gallon drum