

Super S[®] Air Tool Oil

TECHNICAL PRODUCT INFORMATION



Super S Air Tool Oil

Super S Air Tool Oil is designed to lubricate and protect rotary and piston type air tools

FEATURES/ BENEFITS

Super S Air Tool Oil

- Dissolves power robbing deposits
- Improves power output and performance
- Displaces moisture from surfaces
- Protects from rust and corrosion
- Prevents oxidation and deposits

APPLICATIONS

- Use as directed by air tool manufacturers

SPECIAL HANDLING, NOTICES OR WARNINGS

Flammable

Keep away from heat and flame.

Use in well ventilated area

Avoid contact with eyes

Avoid prolonged or repeated contact with skin

Do not induce vomiting

Super S [®] Air Tool Oil		
Property	Test Method ASTM -D	ISO Viscosity Grade
		32
Gravity °API	1298	29
Pour Point, °C/°F	97	-32/-25
Viscosity cSt @ 40°C cSt @ 100°C	445	32 5.3
Viscosity Index	2270	>50
Color	1500	2.0 max
Oxidation Life Hrs to 2.0 Acid No.	943	>2000

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS S148

12/12 oz