

# Super S<sup>®</sup> Limited Slip Gear Oil Additive

## TECHNICAL PRODUCT INFORMATION



### Super S Limited Slip Gear Oil Additive

**Super S Limited Slip Gear Oil Additive** is designed to prevent chattering differentials and improve gear oil performance.

#### FEATURES/ BENEFITS

- Quiets noisy gears
- Prevents Chatter and Slipping
- Reduces Differential noise
- Mixes well with conventional and synthetic GL-5 Gear Oils

#### APPLICATIONS

##### Super S Limited Slip Gear Oil Additive

For use in limited slip, posi-traction and locking differentials,  
Suitable for GM 1052358, Ford M2C118-A, Chrysler 4318060 and most imports

- Not for use in JEEP Quadra-Trac or Quadra-Drive
- Not for use in automatic transmissions or with ATF applications

Add up to 2 oz per quart of either conventional or synthetic GL-5 gear oil

#### RECOMMENDATIONS/SPECIFICATIONS

Suitable for GM 1052358, Ford M2C118-A, Chrysler 4318060 and most imports

- Not for use in JEEP Quadra-Trac or Quadra-Drive
- Not for use in automatic transmissions or with ATF applications

#### SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling as for any petroleum product.

Use protective gloves

Provide adequate ventilation as products have a distinctive sulfur-phosphorous odor.

#### TYPICAL CHARACTERISTICS

Super S Limited Slip Gear Oil Additive		
Property	Test Method ASTM -D	Typical Data
Gravity, °API	1298	
Flash Point, COC °C/°F	92	
Pour Point, °C/°F	97	
Viscosity	445	
cSt @ 40°C		
cSt @ 100°C		
Viscosity Index	2270	

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

#### PRODUCT NUMBERS