

Super S[®] SuperTac Bar & Chain Oil

TECHNICAL PRODUCT INFORMATION



Super S SuperTac Bar & Chain Oil

Super S SuperTac Bar & Chain Oil is formulated with virgin mineral oil and specific additives for today's high speed chain saws. Contains added Tackifier and higher viscosity base oil for better performance under severe operating conditions.

FEATURES/ BENEFITS

- Formulated with high quality base oils and a balanced additive package
- Higher base oil viscosity
- Extra High Tac no sling additive helps keep chain lubricated
- EP (extreme pressure) additives lubricate under heavy load and shock load conditions
- Penetrates the chain: provides start up lubrication
- Resists wear in service
- Resists corrosion in storage

APPLICATIONS

- **Super S SuperTac Bar and Chain Oil** is designed for use in
- All types of chain saws :
 - Residential, commercial and industrial chain saws
 - Hand operated and automatic oilers
 - Adverse operating conditions of the forest products industry
 - Chains, bars, and sprockets

SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling as for any petroleum product.

TYPICAL CHARACTERISTICS

Super S SuperTac Bar & Chain Oil		
Properties	Test Method ASTM-D	Data
		Extreme Tac
Gravity, °API	1298	
Flash Point °C/°F,	92	218/425
Pour Point °C/°F	97	-12/0
Color	1500	3
Viscosity SUS @ 100°F	88	750

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS 90	12/1 quart bottles
SUS 20	6/1 gallon bottles
SUS 19	55 gallon drum
SUS 19bd	bulk/drum
SUS 19bulk	Bulk