



### **Super S Synthetic Automatic Transmission Fluid Dexron<sup>®</sup> VI**

**Super S Synthetic Automatic Transmission Fluid Dexron<sup>®</sup> VI** is a premium quality, high performance formulation of 100% synthetic base oils and a sophisticated additive package designed for use in General Motors automatic transmissions. Dexron<sup>®</sup> VI is the only GM approved specification for GM model years 2006 and newer.

#### **Features/ Benefits**

- **Full synthetic fluid-** provides all the features and benefits of synthetic fluid needed for GM transmissions.
- **Superior all-temperature, year-round protection and performance - Super S Synthetic Automatic Transmission Fluid Dexron<sup>®</sup> VI** remains fluid at extremely low temperatures for cold weather shifting and to eliminate premature wear (especially at start-up) and maintains its properties at high temperatures and under extreme loads and operating conditions.
- **Enhanced anti-wear protection and shear stability - Super S Synthetic Automatic Transmission Fluid Dexron<sup>®</sup> VI** will help to extend the life and service intervals of your transmission, especially for transmissions experiencing more startup and/or shift cycles, or extreme loads or environments.
- **Smoother shifting, protects against shudder -** The synthetic and additive technologies combine to

provide smoother, more consistent shifting performance and provide smooth, positive lockup, reducing shudder.

- **Extended life of service and performance - Super S Synthetic Automatic Transmission Fluid Dexron<sup>®</sup> VI** will maintain its performance for longer than conventional ATF, especially under more demanding conditions.

#### **Applications**

- **Super S Synthetic Automatic Transmission Fluid Dexron<sup>®</sup> VI** fully licensed and approved by General Motors under registration #J-60153
- GM transmissions for Model year 2006 and newer calling for Dexron VI
- Not for use in CVT (Continuously Variable Transmissions) or DCT (Dual Clutch Transmissions) which require specialized fluids.

#### **Recommendations/Specifications**

**Super S Synthetic Automatic Transmission Fluid Dexron<sup>®</sup> VI** is suitable for use in General Motors transmissions model year 2006 and newer calling for Dexron VI.

**Super S Synthetic Automatic Transmission Fluid Dexron<sup>®</sup> VI** is also recommended for any other vehicle manufacturer that calls for Dexron VI.

\*See page 2 for specific applications

#### **Special handling, notices or warnings**

Use the same care and handling as for any petroleum product.



### Typical Characteristics

Super S Synthetic Transmission Fluid Dexron <sup>®</sup> VI		
Properties	Test Method ASTM D-	Typical Results
API Gravity	1298	35.6
Appearance	Visual	Red
Flash Point, COC °C/°F	92	204° C /400°F
Pour Point, °C/°F	97	-45°C/-49°F
Viscosity cSt @ 40°C cSt @ 100°C	445	27.3 6.0
VI	2270	175
Brookfield Viscosity cP @ -40°C	2983	10600

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

### Applications

Acura ATF-Z1	BMW MINI	QAW) JWS 3309	Hyundai/Kia SP-IV
Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1	CAT TO-2	Fuso ATF-II	Hyundai/Kia SP-IV M (SP4-M)
Allison C-3 & C-4	Chrysler/Dodge MOPAR AS 68 RC	Fuso ATF-SPIII	Hyundai/Kia SP-IV-RR
ATF RED 1, RED 1K	(T-IV), JWS 3309	Fuso ATF-A4	Hyundai/Kia SP-III
Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)	Chrysler/Dodge/Jeep 68043742AA	GM9986195 (Aisin AW, JWS 3309)	Hyundai/Kia Dex-II/ SP-II
Audi G 052 162 A1/A2	Daewoo LT 71141	GM TASA	Hyundai/Kia JWS 3314
Audi G 055 025 A2 (JWS 3309)	Daihatsu AMMIX ATF D-II	GM DEXRON <sup>®</sup> -II	Hyundai/Kia NWS 9683
Audi G 052 162 (ZF Lifeguardfluid 5)	Daihatsu AMMIX ATF D-III SP	GM DEXRON <sup>®</sup> -IID	Hyundai/Kia 040000C90SG
(ZF No. S671 090 170)	Esso LT 71141	GM DEXRON <sup>®</sup> -IIE	ISUZU BESCO ATF-II
Audi/VW G 052 990	FIAT T-IV type, JWS 3309	GM DEXRON <sup>®</sup> -IIIG	ISUZU BESCO ATF-III
BMW JWS 3309 (T-IV)	Ford MERCON <sup>®</sup>	GM DEXRON <sup>®</sup> -IIIH	ISUZU BESCO ATF SP
BMW LA2634	Ford MERCON <sup>®</sup> LV (FF-WSS-M2C-	GM DEXRON <sup>®</sup> -VI	ISUZU SCS Fluid
BMW LT71141 (ZF 5 HP 18FL/19FL/24A)	938A/SF, XT-10 QLV)	GM/GMC/Opel/Saturn AW1	Jaguar ATF 3403-M115
BMW ZF 5HP18FL, 5HP24, 5HP30	Ford FNR5	GM/GMC/Opel/Saturn 88863400	Jaguar ATF LT71141, ZF 5HP24
BMW 7045E	Ford M2C138CJ	GM/GMC/Opel/Saturn 88863401	Jaguar ATF 3403, JLM20238
BMW ETL-8072B	Ford M2C166H	Hino Blue Ribbon ATF	JASO M315-2013 1A
	Ford WSS M2C 138CJ, 166H	Honda ATF-Z1 (except in CVTs)	JASO M315-2013 1A-LV
	Ford WSS M2C 922A1, 924A (XT-8-	Honda DW-1	JASO M315-2013 2A

# SuperS<sup>®</sup> Synthetic Dexron<sup>®</sup> VI ATF



## Technical Product Information

KIA ATF SP-II, SP-III, SP-IV, SP-IVM,	Mitsubishi Diaqueen J3	Saturn T-IV (JWS 3309)	Toyota ATF D-III
Red 1	Mitsubishi Diaqueen ATF PA	Scion (all vehicles)	Toyota ATF T-III
Lexus JWS 3309	NAG 1 (Chrysler, Jeep, Cherokee)	Shell 3403, M115, M1375.4, LA 2634	Toyota ATF T-IV
Mazda ATF D-II	Nissan Matic Fluid C	Subaru ATF	Toyota ATF WS
Mazda ATF M-III	Nissan Matic Fluid D	Subaru ATF 5AT	Vickers M2950-S, I-286-S
Mazda ATF M-V	Nissan Matic Fluid J	Subaru DEXRON <sup>®</sup> -II	Voith H55.6335.xx (G607)
Mazda ATF FZ	Nissan Matic Fluid K	Subaru ATF, ATF HP	Volvo CE 97340
Mazda ATF F-1	Nissan Matic Fluid S	Suzuki AT OIL 5D06	VW 5 HP (ZF 5 HP 30)
Mazda ATF S-1	Opel (all vehicles)	Suzuki ATF 2326	VW 5HP (18FL, 30)
Mazda ATF N-1	Peugeot ZF 4HP20	Suzuki ATF 2384K	VW 5HP (19FL, 24A)
MAZDA ATF 3317	Porsche ZF 5HP19FL, ZF 5HP20,	Suzuki JWS 3309	VW G 055 025 A2 (JWS 3309)
MINI COOPER T-IV	LT71141	Suzuki ATF 3314	VW G 052 162 (ZF Lifeguardfluid 5)
Mitsubishi Diaqueen SK	Porsche ATF 3403-M115,	Suzuki ATF 3317	VW TL 521 62
Mitsubishi Diaqueen SP-II	Porsche T-IV (JWS 3309)	Texaco 7045-E	ZF all 3 & 4 speed transmission
Mitsubishi Diaqueen SP-III	Renault Samsung SATF-D	Texaco 8072B	ZF TE-ML 09
Mitsubishi Diaqueen AW	Saab T-IV (JWS 3309)	Texaco N402	ZF TE-ML 11A, 11B
Mitsubishi Diaqueen J2	Saab 93 165 147	Toyota ATF D-II	